

Midgrab Chain Shortener, MIG

Product Features

- Instant mounting and positioning on any part of the chain.
- Shortening in either chain direction; up-down.
- Designed to prevent inadvertent chain disengagement.
- Can be set idle on the chain leg when shortening is not required.
- LC version offers secure mounting with locking set on any desired part of the chain with one chain direction open for shortening.
- CC version offers close-open function in both chain directions for safe retention of the chain.



Locking Devices for Midgrab MIG

Note! The MIG should be used with at least one locking device.

L - fixed locking set

For fixed mounting

Code:

- L-8: B14905
- L-10: B14915
- L-13: B14917



C - close/open locking set

Spring operated locking device. Can be placed either in open or closed position.

Code:

- C-8: B14904
- C-10: B14914
- C-13: B14916



Product Code Guide - Locking options



MIG C



MIG CC



MIG L



MIG LC

MIG with C pins

Art. no.	Code	WLL tonnes*	L	X	Y	Weight kgs
B14303	MIG CC-8-10	2.6	95	50	60	0.7
B14313	MIG CC-10-10	4.0	125	70	77	1.1
B14323	MIG CC-13-10	6.8	150	90	80	2.6

MIG without pins

Art. no.	Code	WLL tonnes*	L	X	Y	Weight kgs
B14300	MIG-8-10	2.6	95	50	60	0.6
B14310	MIG-10-10	4.0	125	70	77	1.0
B14320	MIG-13-10	6.8	150	90	80	2.5

