



803 CE

GOLFARE MASCHIO 8.8
EYE BOLT 8.8
ANNEAU DE LEVAGE MALE 8.8
RINGSCHRAUBEN 8.8



Coefficiente di sicurezza: 4
 Safety ratio: 4
 Coefficient de sécurité: 4
 Sicherheitsfaktor: 4

Avvitare a mano
 To be screwed by hand
 A visser a main
 Von Hand aufschrauben

| Codice Code Code Code | Misura Size Mesure Abmessung | A | B | C | E | F | H | Peso Weight Poids Gewicht |
|--------------------------------|---------------------------------------|-----|-----|-----|----|----|-----|------------------------------------|
| | D x L (mm) | mm | mm | mm | mm | mm | mm | Kg |
| C80306 | M6x13 | 25 | 45 | 25 | 10 | 10 | 45 | 0,090 |
| C80308 | M8x13 | 25 | 45 | 25 | 10 | 10 | 45 | 0,090 |
| C80310 | M10x17 | 25 | 45 | 25 | 10 | 10 | 45 | 0,110 |
| C80312 | M12x21 | 35 | 63 | 35 | 14 | 14 | 62 | 0,270 |
| C80314 | M14x21 | 35 | 63 | 35 | 14 | 14 | 62 | 0,290 |
| C80316 | M16x27 | 35 | 63 | 35 | 14 | 14 | 62 | 0,310 |
| C80318 | M18x27 | 50 | 90 | 50 | 20 | 20 | 90 | 0,840 |
| C80320 | M20x30 | 50 | 90 | 50 | 20 | 20 | 90 | 0,860 |
| C80322 | M22x36 | 50 | 90 | 50 | 20 | 20 | 90 | 0,900 |
| C80324 | M24x36 | 50 | 90 | 50 | 20 | 20 | 90 | 0,900 |
| C80327 | M27x45 | 60 | 108 | 65 | 24 | 24 | 109 | 1,660 |
| C80330 | M30x45 | 60 | 108 | 65 | 24 | 24 | 109 | 1,700 |
| C80333 | M33x54 | 70 | 126 | 75 | 26 | 28 | 128 | 2,000 |
| C80336 | M36x54 | 70 | 126 | 75 | 26 | 28 | 128 | 2,150 |
| C80342 | M42x63 | 80 | 144 | 85 | 30 | 32 | 147 | 4,150 |
| C80348 | M48x68 | 90 | 166 | 100 | 35 | 38 | 168 | 6,200 |
| C80356 | M56x78 | 100 | 184 | 110 | 38 | 42 | 187 | 8,800 |
| C80364 | M64x90 | 110 | 206 | 120 | 42 | 48 | 208 | 12,400 |

WORKING LOAD LIMIT W.L.L (t)



| Codice Code Code Code | Misura Size Mesure Abmessung | 0° | 0° | 0°-45° | 45°-60° | 0°-45° | 45°-60° | Coppia max di serraggio Max tightening couple Max couple de serrage Max Drehmoment |
|--------------------------------|---------------------------------------|---|--|--|--|--|---------|---|
| | | 1 braccio Single leg 1 brin 1 Strang | 2 bracci 2 legs 2 brins 2 Stränge | 2 bracci 2 legs 2 brins 2 Stränge | 2 bracci 2 legs 2 brins 2 Stränge | 3/4 bracci 3/4 legs 3/4 brins 3/4 Stränge | | (Nm) |
| C80306 | M6x13 | 0,4 | 0,8 | 0,14 | 0,1 | 0,2 | 0,14 | 3,5 |
| C80308 | M8x13 | 0,8 | 1,6 | 0,28 | 0,2 | 0,4 | 0,28 | 8 |
| C80310 | M10x17 | 1 | 2 | 0,35 | 0,25 | 0,5 | 0,35 | 16 |
| C80312 | M12x21 | 1,6 | 3,2 | 0,56 | 0,4 | 0,8 | 0,56 | 28 |
| C80314 | M14x21 | 3 | 6 | 1 | 0,75 | 1,5 | 1 | 45 |
| C80316 | M16x27 | 4 | 8 | 1,4 | 1 | 2 | 1,4 | 70 |
| C80318 | M18x27 | 5 | 10 | 1,8 | 1,25 | 2,5 | 1,8 | 95 |
| C80320 | M20x30 | 6 | 12 | 2,1 | 1,5 | 3 | 2,1 | 135 |
| C80322 | M22x36 | 7 | 14 | 2,4 | 1,75 | 3,5 | 2,4 | 182 |
| C80324 | M24x36 | 8 | 16 | 2,8 | 2 | 4 | 2,8 | 230 |
| C80327 | M27x45 | 10 | 20 | 3,5 | 2,5 | 5 | 3,5 | 343 |
| C80330 | M30x45 | 12 | 24 | 4,2 | 3 | 6 | 4,2 | 465 |
| C80333 | M33x54 | 14 | 28 | 4,8 | 3,4 | 6,8 | 4,8 | 632 |
| C80336 | M36x54 | 16 | 32 | 5,6 | 3,9 | 7,8 | 5,4 | 814 |
| C80342 | M42x63 | 24 | 48 | 8,4 | 5,9 | 11,8 | 8,2 | 1304 |
| C80348 | M48x68 | 32 | 64 | 11,2 | 7,8 | 15,6 | 10,9 | 1981 |
| C80356 | M56x78 | 36 | 72 | 12,6 | 8,8 | 17,6 | 12,3 | 3000 |
| C80364 | M64x90 | 45 | 90 | 15,7 | 11 | 22 | 15,4 | 4736 |