


Features & benefits


- Pointer damped with glycerine
- Stainless steel
- Housing Ø 100 mm
- Connection: 1/2" NPT male

Pressure gauges - Scale division in ton


model	A 501	A 502	A 503	A 504	A 505	A 506
art no	100.582.501	100.582.502	100.582.503	100.582.504	100.582.505	100.582.506
1st scale range	t 5	25	52	105	210	509
2nd scale range	t 11	33	77	160	305	382
3rd scale range	t 21	51				
1st scale division per mark	kg 100.0	500.0	1000.0	2000.0	5000.0	10000.0
2nd scale division per mark	kg 200.0	500.0	1000.0	2000.0	5000.0	10000.0
3rd scale division per mark	kg 500.0	1000.0				
connection	1/2" NPT male	1/2" NPT male	1/2" NPT male	1/2" NPT male	1/2" NPT male	1/2" NPT male
material	stainless steel	stainless steel	stainless steel	stainless steel	stainless steel	stainless steel
housing diameter	mm 100	100	100	100	100	100

Pressure gauges - Scale division in ton


model	A 507	A 508	A 509	A 510
art no	100.582.507	100.582.508	100.582.509	100.582.510
1st scale range	t 6	30	63	12
2nd scale range	t 12	47	104	31
3rd scale range	t 23	63		63
4th scale range	t	113		98
1st scale division per mark	kg 100.0	500.0	1000.0	200.0
2nd scale division per mark	kg 200.0	1000.0	2000.0	500.0
3rd scale division per mark	kg 500.0	1000.0		2000.0
4th scale division per mark	kg	2000.0		2000.0
connection	1/2" NPT male	1/2" NPT male	1/2" NPT male	1/2" NPT male
material	stainless steel	stainless steel	stainless steel	stainless steel
housing diameter	mm 100	100	100	100