

pewag KHSWP Clevis sling hook

Resistance on a large scale.

This is a completely new hook in the pewag winner pro G12 range with a considerably larger jaw size than the HSWP eye sling hook.

It is manufactured according to EN 1677-2 with the mechanical values of grade 12 and may be mounted directly into the chain in the pewag winner pro clevis system without the need for a connecting link. The forged safety catch locks into the tip of the hook, thereby providing excellent protection against lateral shifts. The safety catch mechanism and the clevis load pins are available as spare parts set and easy and quick to exchange by a competent person.

The forged control markings make it easy to determine discard criteria.



| KHSWP Clevis sling hook | Code | le Load capacity [kg] | е | h | а | d | g1 | b | Weight |
|-------------------------|----------|-----------------------------|------|------|------|-------|------|------|----------|
| | | | [mm] | [mm] | [mm] | [mm] | [mm] | [mm] | [kg/pc.] |
| 8 1 1 | KHSWP 7 | 2,360 | 105 | 26 | 19 | 9.50 | 36 | 101 | 0.85 |
| | KHSWP 8 | 3,000 | 105 | 26 | 19 | 10.70 | 36 | 101 | 0.85 |
| | KHSWP 10 | 5,000 | 121 | 33 | 26 | 14 | 41 | 118 | 1.68 |
| | KHSWP 13 | 8,000 | 148 | 43 | 30 | 17.50 | 49 | 147 | 2.99 |
| | KHSWP 16 | 12,500 | 173 | 51 | 35 | 21 | 59 | 176 | 5.10 |