

ALUMINIUM TRIPOD



- Light aluminium construction
- Simple transport due to telescopic height adjustment
- Spikes as standard
- Equipped with swivelling suspension eye

Accessories:

- Rubber plates (for solid ground)
- Safety chain (for smooth ground)
- Hoist

Order No.	Model	Carrying Capacity kg	Length Of Support L Min./Max. m	Clearance Height ¹⁾ H Min./Max. m	Spreading Angle ¹⁾ B Min./Max. m	Weight Approx. kg
140 001	D-250	250	1,18 / 1,88	0,94 / 1,58	0,94 / 1,50	10
140 009F	D-250 Mobile	250	1,85 / 3,10	1,46 / 2,57	1,40 / 2,40	36
140 003	D-500	500	1,50 / 2,50	1,15 / 2,05	1,20 / 1,95	17
140 033	D-500/EN795 ²⁾	500	1,50 / 2,50	1,15 / 2,05	1,20 / 1,95	17
140 009	D-503	500	1,76 / 3,00	1,45 / 2,63	1,43 / 2,39	20
140 008	D-1000	1.000	1,78 / 3,00	1,38 / 2,54	1,65 / 2,35	27
140 014	D-1004	1.000	2,25 / 4,00	1,86 / 3,44	1,79 / 3,07	36

²⁾ Permitted for man riding applications up to 150 kg according to EN 795. Equipped with rubber plates and safety chain.

¹⁾ Max. spreading angle (25°)

Suitable man riding rope lifting and lowering equipment available.